

PR SPRAY

Page: 1

**Revision date:** 12/02/2018

**Revision No: 7** 

# Section 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name: PR SPRAY

# 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Mould Release Spray

# 1.3. Details of the supplier of the safety data sheet

Company name: ROCOL

ROCOL House Swillington

Leeds

West Yorkshire LS26 8BS ENGLAND

**Tel:** +44 (0) 113 232 2700 **Fax:** +44 (0) 113 232 2740

Email: <a href="mailto:customer-service@rocol.com">customer-service@rocol.com</a>

# 1.4. Emergency telephone number

Emergency tel: +44 (0) 113 232 2600

#### **Section 2: Hazards identification**

# 2.1. Classification of the substance or mixture

Classification under CLP: Skin Irrit. 2: H315; Aquatic Chronic 3: H412; Flam. Aerosol 1: H222; -: H229

Most important adverse effects: Extremely flammable aerosol. Pressurised container: May burst if heated. Causes skin

irritation. Harmful to aquatic life with long lasting effects.

# 2.2. Label elements

Label elements:

Hazard statements: H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

H315: Causes skin irritation.

H412: Harmful to aquatic life with long lasting effects.

Hazard pictograms: GHS02: Flame

GHS07: Exclamation mark





PR SPRAY

Page: 2

Signal words: Danger

Precautionary statements: P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122

°F.

P251: Do not pierce or burn, even after use.

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P211: Do not spray on an open flame or other ignition source.

P285: In case of inadequate ventilation wear respiratory protection.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352: IF ON SKIN: Wash with plenty of water.

#### 2.3. Other hazards

**PBT:** This product is not identified as a PBT/vPvB substance.

# Section 3: Composition/information on ingredients

# 3.2. Mixtures

# **Hazardous ingredients:**

HYDROCARBON AEROSOL PROPELLANT (<0.1% 1,3-BUTADIENE) - REACH registered number(s): EXEMPT

EINECS	CAS	PBT / WEL	CLP Classification	Percent
270-704-2	68476-85-7	Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	50-75%

HEPTANE & ISOMERS - REACH registered number(s): 01-2119475515-33

927-510-4	64742-49-0	-	Flam. Liq. 2: H225; Aquatic Chronic 2:	10-25%	
			H411; Skin Irrit. 2: H315; STOT SE 3:		
			H336; Asp. Tox. 1: H304		

### Section 4: First aid measures

#### 4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash

immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Consult a doctor. May be harmful if swallowed and enters

airways

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a

doctor.

# 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat.

PR SPRAY

Page: 3

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may

cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

# 4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

#### Section 5: Fire-fighting measures

# 5.1. Extinguishing media

**Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used. Use water spray

to cool containers.

#### 5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

# 5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

#### Section 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from

downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn

leaking containers leak-side up to prevent the escape of liquid.

# 6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

#### 6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method.

#### 6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

### Section 7: Handling and storage

# 7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Do not handle in a confined space. Avoid the formation or spread of mists in the air.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

PR SPRAY

Page: 4

### 7.3. Specific end use(s)

Specific end use(s): No data available.

#### Section 8: Exposure controls/personal protection

#### 8.1. Control parameters

# **Hazardous ingredients:**

# **HYDROCARBON AEROSOL PROPELLANT (<0.1% 1,3-BUTADIENE)**

#### Workplace exposure limits:

#### Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	1000ppm 1750 mg/m3	1250ppm 2180 mg/m3	-	-

#### **HEPTANE & ISOMERS**

UK	500 ppm, 2085 mg/m3	-	-	-
----	---------------------	---	---	---

# **DNEL/PNEC Values**

**DNEL / PNEC** No data available.

#### 8.2. Exposure controls

**Engineering measures:** Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Protective gloves. Nitrile gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Environmental: No data available

# Section 9: Physical and chemical properties

# 9.1. Information on basic physical and chemical properties

State: Aerosol
Colour: Colourless

Odour: Characteristic odour

Evaporation rate: Fast

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Insoluble

Viscosity: Non-viscous

Boiling point/range°C: < 0 Melting point/range°C: < 0

Flammability limits %: lower: 1.8 upper: 9.4

Flash point°C: <-100 Part.coeff. n-octanol/water: No data available.

Autoflammability°C: > 200 Vapour pressure: No data available.

Relative density: 0.6 pH: No data available.

VOC g/l: 546

PR SPRAY

Page: 5

#### 9.2. Other information

Other information: No data available.

#### Section 10: Stability and reactivity

### 10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

# 10.2. Chemical stability

Chemical stability: Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

#### 10.4. Conditions to avoid

Conditions to avoid: Heat.

#### 10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

# 10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

# **Section 11: Toxicological information**

# 11.1. Information on toxicological effects

#### Hazardous ingredients:

### **HEPTANE & ISOMERS**

DERMAL	RBT	LD50	>2000	mg/kg
ORAL	RAT	LD50	>5000	mg/kg
VAPOURS	HMN	4H LC50	>20	mg/l

#### Relevant hazards for product:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated

# Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may

cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

PR SPRAY

Page: 6

# Section 12: Ecological information

# 12.1. Toxicity

# **Hazardous ingredients:**

#### **HEPTANE & ISOMERS**

ALGAE	96H ErC50	> 10 - < 100	mg/l
DAPHNIA	96H ErC50	>1 - < 10	mg/l
Daphnia magna	96H ErC50	> 10 - < 10	-
FISH	96H LC50	>1 - < 10	mg/l

### 12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

# 12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

#### 12.4. Mobility in soil

Mobility: Readily absorbed into soil.

# 12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

# 12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

# Section 13: Disposal considerations

# 13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

Recovery operations: No data available

Waste code number: 16 05 05

**Disposal of packaging:** Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

# **Section 14: Transport information**

# 14.1. UN number

UN number: UN1950

# 14.2. UN proper shipping name

Shipping name: AEROSOLS, FLAMMABLE

PR SPRAY

Page: 7

# 14.3. Transport hazard class(es)

Transport class: 2.1

#### 14.4. Packing group

Packing group: n/a

#### 14.5. Environmental hazards

Environmentally hazardous: No Marine pollutant: No

#### 14.6. Special precautions for user

Special precautions: No special precautions.

# 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Transport in bulk: No data available.

### **Section 15: Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: No data available

# 15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

#### **Section 16: Other information**

# Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

2015/830.

Safety data sheet prepared in accordance with Commission Directive 2008/47/EC of 8

April 2008 amending, for the purposes of adapting to technical progress, Council

Directive 75/324/EEC relating to aerosol dispensers

Compiled in accordance with REACH.

Phrases used in s.2 and s.3: H220: Extremely flammable gas.

H222: Extremely flammable aerosol.

H225: Highly flammable liquid and vapour.

H229: Pressurised container: May burst if heated.

H280: Contains gas under pressure; may explode if heated.

H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H336: May cause drowsiness or dizziness.

H411: Toxic to aquatic life with long lasting effects.

H412: Harmful to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

PR SPRAY

Page: 8

and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.