



SAFETY DATA SHEET
SAFE STEP 100 - ALL COLOURS

Page: 1

Compilation date: 27/05/2015

Revision date: 16/01/2019

Revision No: 3

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: SAFE STEP 100 - ALL COLOURS

Product code: 432(66,67,77)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Anti-Slip Floor Coating

1.3. Details of the supplier of the safety data sheet

Company name: ROCOL

ROCOL House

Swillington

Leeds

West Yorkshire

LS26 8BS

ENGLAND

Tel: +44 (0) 113 232 2700

Fax: +44 (0) 113 232 2740

Email: customer-service@rocol.com

1.4. Emergency telephone number

Emergency tel: +44 (0) 113 232 2600

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Flam. Liq. 3: H226; Skin Irrit. 2: H315; -: EUH208

Most important adverse effects: Contains (cas 100545-48-0) octadecanoic acid, 12-hydroxy-, reacted with ethylendiamine. May produce an allergic reaction. Flammable liquid and vapour. Causes skin irritation.

2.2. Label elements

Label elements:

Hazard statements: EUH208: Contains (cas 100545-48-0) octadecanoic acid, 12-hydroxy-, reacted with ethylendiamine. May produce an allergic reaction.

H226: Flammable liquid and vapour.

H315: Causes skin irritation.

Hazard pictograms: GHS02: Flame

GHS07: Exclamation mark

[cont...]

SAFETY DATA SHEET

SAFE STEP 100 - ALL COLOURS

Page: 2



Signal words: Warning

Precautionary statements: P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P241: Use explosion-proof electrical/ventilating/lighting/... equipment.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352: IF ON SKIN: Wash with plenty of water.
P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water .
P321: Specific treatment (see instructions on this label)

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

XYLENE - REACH registered number(s): 01-2119488216-32-XXXX

EINECS	CAS	PBT / WEL	CLP Classification	Percent
215-535-7	1330-20-7	-	Flam. Liq. 3: H226; Acute Tox. 4: H332; Acute Tox. 4: H312; Skin Irrit. 2: H315	20-30%

ETHYLBENZENE

202-849-4	100-41-4	-	Flam. Liq. 2: H225; Acute Tox. 4: H332; STOT RE 2: H373; Asp. Tox. 1: H304	1.0-10%
-----------	----------	---	--	---------

(CAS 100545-48-0) OCTADECANOIC ACID, 12-HYDROXY-, REACTED WITH ETHYLENDIAMINE - REACH registered number(s): 01-2119979085-27-XXXX

309-629-8	100545-48-0	-	Skin Sens. 1B: H317; Aquatic Chronic 3: H412	<0.3%
-----------	-------------	---	--	-------

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water. Remove all contaminated clothes and footwear immediately unless stuck to skin. Obtain medical attention if soreness or redness persists.

Eye contact: Bathe the eye with running water for 15 minutes. Obtain medical attention if soreness or redness persists.

Ingestion: Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Seek medical attention if you feel unwell.

[cont...]

SAFETY DATA SHEET

SAFE STEP 100 - ALL COLOURS

Page: 3

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Seek medical attention if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. There may be vomiting.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: No data available.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Carbon dioxide. Dry chemical powder. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Flammable. In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Turn leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of ignition.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Mix with sand or vermiculite. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS. Refer to section 13 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Smoking is forbidden.

[cont...]

SAFETY DATA SHEET
SAFE STEP 100 - ALL COLOURS

Page: 4

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): Anti-slip Floor Coating

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

XYLENE

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	220 mg/m ³	441 mg/m ³	-	-

ETHYLBENZENE

UK	441 mg/m ³	552 mg/m ³	-	-
----	-----------------------	-----------------------	---	---

DNEL/PNEC Values

Hazardous ingredients:

XYLENE

Type	Exposure	Value	Population	Effect
DNEL	Inhalation	289	Workers	Systemic
DNEL	Dermal	180	Workers	Systemic
DNEL	Inhalation (repeated dose)	77	Workers	Systemic
DNEL	Inhalation (repeated dose)	174	Consumers	Systemic
DNEL	Inhalation (repeated dose)	174	Consumers	Local
DNEL	Dermal	108	Consumers	Local
DNEL	Inhalation	14.8	Consumers	Local
PNEC	Fresh water	0.327	-	-
PNEC	Marine water	0.327	-	-
PNEC	Microorganisms in sewage treatment	6.58	-	-
PNEC	Fresh water sediments	12.46	-	-
PNEC	Marine sediments	12.46	-	-
PNEC	Soil (agricultural)	2.31	-	-

[cont...]

SAFETY DATA SHEET
SAFE STEP 100 - ALL COLOURS

Page: 6

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

XYLENE

ORL	MUS	LD50	2119	mg/kg
ORL	RAT	LD50	4300	mg/kg
SCU	RAT	LD50	1700	mg/kg

ETHYLBENZENE

IPR	MUS	LD50	2624	µl/kg
ORL	RAT	LD50	3500	mg/kg

Relevant hazards for product:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. There may be vomiting.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: No data available.

Other information: Not applicable.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

(CAS 100545-48-0) OCTADECANOIC ACID, 12-HYDROXY-, REACTED WITH ETHYLENDIAMINE

Daphnia magna	48h EL50	>10mg/l	-
RAINBOW TROUT (Oncorhynchus mykiss)	96h LL50	>10mg/l	-

12.2. Persistence and degradability

Persistence and degradability: Biodegradable in part only.

[cont...]

SAFETY DATA SHEET
SAFE STEP 100 - ALL COLOURS

Page: 7

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

Persistence (P-):

Persistence result: not P-

Bioaccumulation (B-):

Bioaccumulation result: not B-

Toxicity (T-):

mg/l

NOEC for marine or freshwater organisms: >0.1

Toxicity result: not T-

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: No data available.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Incineration on land.

Recovery operations: Solvent reclamation/regeneration.

Waste code number: 08 01 11

Disposal of packaging: Dispose of as normal industrial waste.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1263

14.2. UN proper shipping name

Shipping name: PAINT RELATED MATERIAL

14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

Packing group: III

[cont...]

SAFETY DATA SHEET
SAFE STEP 100 - ALL COLOURS

Page: 8

14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: No

14.6. Special precautions for user

Tunnel code: D/E

Transport category: 3

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

Compiled in accordance with REACH.

Phrases used in s.2 and s.3: EUH208: Contains (cas 100545-48-0) octadecanoic acid, 12-hydroxy-, reacted with ethylenediamine. May produce an allergic reaction.

H225: Highly flammable liquid and vapour.

H226: Flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H312: Harmful in contact with skin.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H332: Harmful if inhaled.

H373: May cause damage to organs through prolonged or repeated exposure.

H412: Harmful to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.